



TO PROGRAM NEW GAP SETTING – STRIP BACON

1. **PRESS** and **HOLD** the **"PROG"** button for **five, (5), seconds**. (Display will flash GC450 and the program version number).
2. **PRESS** the **"PROG"** button **twice** to display **"SYSTEM SETUP."**
3. **PRESS** and **HOLD** the **"UP ARROW"** button (↑) for **ten (10) seconds**, **"GAP CALIBRATION"** will be displayed.
4. **PRESS** the **"PROG"** button **twice** to display **"MENU ITEMS."**
5. **PRESS** the **"MENU"** button to display **"STRIP BACON – CLAM"**.
6. **PRESS** the **"FUNCTION"** button to obtain **"GAP SETTING - .090"**.
7. **PRESS** the **"UP ARROW"** button (↑) to change the flashing "0" to "2".
8. **PRESS** the **"RIGHT ARROW"** button (→) **to move the cursor**, (blinking digit), to the second position.
9. **PRESS** the **"UP ARROW"** button (↑) to change the flashing "9" to "6".
10. **PRESS** the **"RIGHT ARROW"** button (→) **to move the cursor**, (blinking digit), to the third position.
11. **PRESS** the **"UP ARROW"** button (↑) to change the flashing "0" to "5".
12. **PRESS** the **"FUNCTION"** button to display **"ALARM"**.
13. **PRESS** the **"PROG"** button to display **"MENU ITEMS"**.
14. **PRESS** the **"RIGHT ARROW"** button (→) to return to the normal **OPERATING MODE**.